

Amaircare AirWashPRO air scrubbing systems effectively provide filtration for abatement, industrial, healthcare and renovation applications.

Four-Stage Filtration

Stage 1: Media Pad Prefilter & MERV 8 Pleated Prefilter

Removes Large Dust Particles – Disposable.

Stage 2: 14" Washable Foam Filter

Captures small and medium dust particles that pass through the first stage filter. Extends the life of the HEPA filter. (Note after some applications it is recommended that all the filters are disposed of rather than cleaned)

Stage 3: 14" HEPA Filter

99.97% efficient @ 0.3 microns. Removes dust, pollen, bacteria, dander, attached viruses, cigarette smoke, radon daughters and more.

Optional

Stage 4: Inner Carbon 14" V.O.C. Blanket OR

5 lbs V.O.C. canister

Removes gas molecules, including V.O.C.'s that could be hazardous.

No Tools Needed

Filters can be accessed and changed without any tools required.

Stackable Up to 2 units. Saves floor space.

Daisy-Chain Power Outlet

Removable Filter Cabinet

makes for easy to change filters and easy cleaning between uses.

2 Carry Options

1 flexible handle at the top of the unit and 2 moulded handles on the side of the unit.

Rubber Feet

minimize vibration.

AMAIRCARE Model AirWash MultiPRO 120VAC Air Scrubbing Filtration System

SPECIFICATIONS

CLASSIFICATION

 Portable HEPA (High Efficiency Particulate Arrestance) 100% Sealed Air Cleaning Device

DIMENSIONS: 19"W x 20"H x 32"L

WEIGHT: 42 lbs

AIR FLOW (C.F.M.): 800 CFM delivered (nominal on HIGH)

POWER USAGE: 2.6 AMPS

HEPA MATERIAL: 100 sq.ft.

FINISH: Rotomold Plastic, Meets CSA 22.2 No 0.6 flammability requirements for polymer cabinets housing energized electrical components

COLOR(S): Grey

SERVICE AREA: 5,175 sq ft (1 ACH per Hour)

INTAKE: 12" Round

OUTFLOW: 12" Round with safety screen

REMOVABLE FILTER CABINET

FLEXIBLE HANDLE

VARIABLE SPEED CONTROL WITH FILTER CHANGE INDICATOR LIGHTS and DAISY-CHAIN POWER OUTLET

12" D OUTFLOW WITH SAFETY SCREEN

MOULDED SIDE HANDLES

MOULDED TO STACK

CONVENIENT ELECTRICAL CORD WRAP TABS

VIBRATION ABSORBING FEET

SUPPLY: 120 VAC/1 phase/60 HZ Grounded CONTROL: OFF/ON Variable Speed with indicating lights for power ON and Filter Change

www.amaircare.com

- **PROTECTION:** Resistible thermal circuit breaker, thermally protected motor, accessory receptacle with ground fault, circuit Interrupter (12 AMP 120 VAC Accessory Load)
- **CERTIFICATIONS:** This equipment meets the technical requirements of CSA C22.2 No. 0,0.4, CSA Model Code SPE 1000 and CE 2015

FILTER OPTIONS

- Inner Carbon V.O.C. Blankets
- 5 lb Granulated Carbon Canister (replaces 4th stage inner carbon blanket) added odor absorption
- 25 lb Upgraded Carbon Canister (replaces 3rd stage HEPA cartridge) for extreme odor absorption

airwas

Cleaning the air you breathe.